




Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC



The CLIC way to a multi-TeV linear collider - Basic features


- High acceleration gradient (100 MV/m)

 - ✓ "Compact" collider - overall length @ 3 TeV < 50 km



 - ✓ Normal conducting accelerating structures

 - ✓ High acceleration frequency (12 GHz)




- Two-Beam Acceleration Scheme



 - ✓ Cost effective, reliable, efficient

 - ✓ Simple tunnel, no active elements


 - ✓ Modular, easy energy upgrade in stages





Robert H. Siemann



CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop


The CLIC Two-Beam Accelerator






Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop




CLIC schematic layout @ 3 TeV




Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop




CLIC RF power source

CLIC schematic layout @ 3 TeV



Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

The CLIC scheme - What does the RF Power Source do ?


The CLIC RF power source can be described as a “black box”, combining *very long RF pulses*, and transforming them in *many short pulses*, with *higher power* and with *higher frequency*





Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop


Full beam-loading acceleration in TW sections





Robert H. Siemann



CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Full beam-loading acceleration in TW sections




Time resolved beam energy spectrum measurement in CTF3





Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop


Beam combination/separation by transverse RF deflectors





Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop


Beam combination/separation by transverse RF deflectors





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Counter flow distribution

Counter propagation from central complex

Instead of using a single drive beam pulse for the whole main linac, several ($N_S = 24$) short ones are used. Each one feed a 900 m long sector of TBA.



(DLDS-like system)


Counter-flow distribution allows to power different sectors of the main linac with different time bins of a single long electron pulse.

The distance between pulses is $2 L_S = 2 L_{main}/N_S$. The initial drive beam pulse length is equal to $2 L_{main} = 140 \mu\text{s}/c$.



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Use of CLIC-like drive beam in Plasma Wakefield Accelerator




A. Seryi – PAC 09




Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009


R. Siemann Symposium and ICFA Mini-Workshop



Drive beam time structure - initial




Drive beam time structure - final





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Phase coding


How to "code" the sub-pulses



Gap creation & first multiplication $\times 2$

$$L_{delay} = n \lambda_0 = c T_{sub-pulse}$$


Combination scheme





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009



RF injection in combiner ring


$$C_{ring} = (n + 1/4) \lambda$$





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009


R. Siemann Symposium and ICFA Mini-Workshop

CTF3 preliminary phase (2001-2002)

Transition through zero momentum compaction optics - $\alpha \leq 10^{-4}$



streak camera measurement



Beam structure after combination (factor 4)

Experiment was performed in 2002, *at low current and short pulse*, in the CERN Electron Positron Accumulator (EPA), properly modified


Bunch spacing
83 ps

Pulse Length 6.6 ns
Beam Peak Current 1.2 A



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

RF injection in combiner ring in CTF3 preliminary phase (2001-2002)




Streak camera images of the beam, showing the bunch combination process




Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC



The CLIC Test Facility CTF3


is a small scale version of the CLIC drive beam complex





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC







R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop



The CTF3 – CLIC world wide collaboration

28 institutes involving 18 funding agencies from 16 countries



Ankara University (Turkey)
 BINP (Russia)
 CERN
 CIEMAT (Spain)
 Cockcroft Institute (UK)
 Gazi Universities (Turkey)
 IRFU/Saclay (France)

Helsinki Institute of Physics (Finland)
 IAP (Russia)
 IAP NASU (Ukraine)
 Instituto de Fisica Corpuscular (Spain)
 INFN / LNF (Italy)
 J.Adams Institute, (UK)
 JINR (Russia)


JLAB (USA)
 Karlsruhe University (Germany)
 KEK (Japan)
 LAL/Orsay (France)
 LAPP/ESIA (France)
 NCP (Pakistan)
 North-West. Univ. Illinois (USA)

Oslo University (Norway)
 PSI (Switzerland),
 Polytech. University of Catalonia (Spain)
 RRCAT-Indore (India)
 Royal Holloway, Univ. London, (UK)
 SLAC (USA)
 Uppsala University (Sweden)



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

- ✓ Provide RF power to test accelerating structures and components
- ✓ Full beam-loading accelerator operation
- ✓ Electron beam recombination by RF injection at high current
- ✓ Safe and stable beam deceleration and power extraction
- ✓ Two-beam acceleration scheme




- Structures
- Structure materials
- Drive Beam generation
- PETS on-off
- DB decelerator
- CLIC sub-unit



Robert H. Siemann



CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Drive Beam linac – high current, full beam loading operation




efficiency



Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC





R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Direct measurement of efficiency at CTF3:

Setup: Adjust RF power and phase in all klystrons to beam current, such that fully loaded condition is fulfilled




- Method:**
- Measure RF power, current and initial/final beam energy.
 - Switch off one klystron at a time and measure relative energy in spectrometer 10.
 - Check consistency and compare with calculations.

measured RF-to-beam efficiency: 95.3 %
 Theory: 96% (~4 % ohmic losses)



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Fast phase switch from SHB system (CTF3)





3 TW Sub-harmonic bunchers, each fed by a wide-band TWT



6-cell 1.5 GHz buncher structure

Streak camera image




$8.5 \cdot 666 \text{ ps} = 5.7 \text{ ns}$



Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC






R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Delay Loop – beam current multiplication x 2, hole creation


Beam current measured:





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009



R. Siemann Symposium and ICFA Mini-Workshop

Combiner Ring

Fast vertical beam instability in CTF3 solved by new deflectors with strong damping of the vertical deflecting mode and larger hor./vert. detuning




Old RF deflectors



New RF deflectors (INFN-Frascati)


Bukit in Aluminium – very fast conditioning to nominal power (1 day)





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop


Without the losses from the fast vertical beam instability (plus improved optics control and tuning tools) it is now possible to circulate the 3 A beam with very small losses for hundreds of turns.

Combiner Ring



Bunch re-combination of a 3 A beam with factor four current increase had been demonstrated – 12 A reached.


(DL still by-passed, and limited by RF pulse length)





Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop


CLIC Power Flow





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

CLIC Power Consumption Breakdown

Main beam magnets	Grid power [MW]
Injector linacs	1.2
Positron pre-damping ring	0.8
Electron pre-damping ring	0.3
Damping rings warm magnets	2.2
Damping ring SC wigglers	0.5
Surface to tunnel transfer	2.1
Return lines	1.0
Turn arounds	2.2
Main linacs	8.4
Beam delivery system	3.0
Spent beam lines	4.1
Main beam magnets total	25.8
Main Beam Injector RF	
Positron production linac	0.5
Main beam linacs 2.4 and 9 GeV	1.8
Pre-damping rings	6.5
Damping rings	6.5
Main beam injector RF total	15.2


Drive beam magnets	Grid power [MW]
DB Accelerator	0.4
Delay loops	1.2
Combiner rings 1	1.3
Combiner rings 2	1.3
Surface to tunnel transfer	1.3
Return lines	0.3
Turn arounds	32.7
Decelerators	7.7
Beam dumps	0.5
Drive beam magnets total	46.7
Drive beam linac RF	
Modulator auxiliaries	7.8
RF power	255.5
Drive beam linac RF total	263.3
Beam, RF and alignment instrumentation	5.0
Detector	15.0
Water systems	9.8
Ventilation systems	8.8
Tunnel infrastructure	2.5
Grand total	392.1

Table 11: CLIC 3 TeV power consumption



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009



Energy spread in full beam-loading regime



Initial transient


- Can be kept to a few percent level by RF delayed filling of DBA structures
- In CLIC, small fraction of the pulse – will be lost in a controlled way at the end of the DBA

- Any drive beam current variation will result in a corresponding variation in final drive beam energy
- That's why in CLIC we accelerate a long (140 μs) constant current drive beam pulse, and only split/recombine it after acceleration



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

Energy spread in full beam-loading regime



Constant current drive beam pulse
with duration $\gg t_{\text{fill}}$




Steady state after t_{fill}



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009




Energy spread in full beam-loading regime



Drive beam pulses with duration $> t_{\text{fill}}$
spaced by $\Delta t > t_{\text{fill}}$


“Short” steady states





Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009


R. Siemann Symposium and ICFA Mini-Workshop

Energy spread in full beam-loading regime



Drive beam pulses with duration $< t_{\text{fill}}$
spaced by $\Delta t < t_{\text{fill}}$


quasi steady-state (“filtering”)





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

Energy spread in full beam-loading regime

E. Jensen-D.Schulte, CLIC ACE May 2009


- Drive beam phase jitter leads to luminosity drop.
- $\Delta\varphi$ at 1 GHz causes 12 $\Delta\varphi$ at 12 GHz!
- Any R_{56} transforms drive beam energy jitter to phase jitter.
- With full beam loading, drive beam current error transforms to energy error (and then phase error).
- Requirement (order of magnitude):
 - drive beam phase jitter $< 0.02^\circ$ (3.5E-4, 50 fs)
 - drive beam energy jitter $< \mathcal{O}(1E-4)$
 (With a feed-forward, this may be relaxed by a factor 10!)
- Accelerating structures and recombination scheme act as filters for the noise.

Filtering of drive beam current variations

Filtering of klystron power variations

- filtering the klystron signal:

$$\left| \frac{V_{acc}}{\sqrt{P_{klystron}} / (33 \text{ MW})} \right|$$




τ_{full}^{-1}

$\frac{f - f_c}{\text{GHz}}$

- filtering the beam signal:

$$\left| \frac{V_{acc}}{I_{beam} / (4.21 \text{ A})} \right|$$




τ_{full}^{-1}

$\frac{f - f_c}{\text{GHz}}$



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC




R. Corsini, 7.7.2009

If the beam is split/recombined like in the CLIC scheme, there is an additional filtering effect


Re-combination transfer function



Total transfer function



τ_{fill}^{-1} τ_{DL}^{-1} Generic




$\tau_{fill}^{-1} = \tau_{DL}^{-1}$ Optimized



Robert H. Siemann


CTF3, Drive Beam Efficiency and use in PWFA-LC



R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop


Some drive beam issues for multi-stage PWFA Linear Collider





Robert H. Siemann

CTF3, Drive Beam Efficiency and use in PWFA-LC





R. Corsini, 7.7.2009

R. Siemann Symposium and ICFA Mini-Workshop

CLIC-like drive beam as a PWFA collider driver – time structure

A. Seryi – CLIC Workshop 2008

Single train for e+ and e- sides
Separation by RF deflectors



Kickers with ~100 ns rise time
Possibility for feed-forward
Plasma cell spacing $c \cdot 600 \text{ ns} / 2$

NB: DBA fill time ~ 250 ns

animation of beam drive distribution:

